# NEC recommends Windows Vista® Business














- The latest Intel<sup>®</sup> Technology
- 3 different chassis available for maximum adaptability
- Ease of manageability
- Excellent platform stability
- · Guaranteed reliability thanks to integrated RAID

www.nec-computers.com



# NEC PowerMate ML470

# THE LATEST MANAGEABILITY TECHNOLOGY FOR PROFESSIONALS

PROCESSOR	
Type:	Intel® Celeron 4xx
	Intel® Pentium Dual Core E2xxx
	Intel® Core™ 2 E 4xxx, E 6xxx
	Intel® Core™ 2 Quad
	Socket LGA775

## OPERATING SYSTEM

Genuine Microsoft® Windows® XP Pro Genuine Microsoft® Windows® XP Home Genuine Windows Vista® Business Genuine Windows Vista® Home Basic

# ARCHITECTURE & MOTHERBOARD

Torride	(DT & MT Chassis)
Chipset:	
North Bridge	Q35
South Bridge	ICH9 DO
Processor Bus	800 / 1066 / 1333 Mhz
MEMORY	
Type:	DDR2 667/800 MHz
Memory Max	Up to 4GB in SFF Chassis &
	8GR in DT & MT Chassis

nBTX (SFF Chassis) & uBTX

2 DIMMs (SFF Chassis) & 4

DIMMs (DT & MT Chassis)

DVD - 48X/16X or above

# VIDE0

Memory Slots:

Format

Integrated Intel Graphics Media Accelerator 3100 up to 256MB shared memory

 $Small\ Desktop\ /\ Micro-Tower\ Chassis$ 

- nVidia® 7100GS 128MB & 256MB
- nVidia® Quadro NVS285 • ADD2 DVI-D Board

#### **STORAGE**

HDD:	From 80GB to 250GB
HDD interface:	SATA2 (RAID 0/1 available)
HDD Speed:	7200 rpm

#### **OPTICAL DEVICES**

(MT & DT)	
Combo Drive (DVD & CDF	W.
DVD+R9	

## CONNECTORS

Audio Controller:	Integrated HDA Azalia Audio
SOUND	
PCI Express x16x	1 in SFF / DT / MT
PCI Express x4x	1 in DT & MT
PCI	2 in DT & MT Chassis

# **BIOS**

DMI 2.3 Compatible
Upgradable by flash

# I/O Ports

JSB Po	orts:	8	USB	2.0	(6	at	rear	&	2	at

#### Front)

PS/2 2 (1 for Keyboard & 1 for

Mouse)

LAN RJ 45 port: 1
VGA port: 1
Line in / Line out /

Mic in 1/1/1

Serial ports 1 (+1 optional)
Parallel port 1

NETW0RK

LAN: Intel 82566DM Gigabit LAN

#### PHYSICAL SPECIFICATIONS

Size (W X D X H):	Microtower: 170 x 424 x 391 mm
	SFF: 92 x 307 x 347 mm
	Small Deskton : 371 x 386 x 102 mr

Weight (With PSU): SFF: 5.1 Kg

Small Desktop: 5.4 Kg Micro-Tower: 5.4 Kg

Operating Constraints: 5-35° C

18-85% Humidity 0-3000 m Altitude

#### **SECURITY**

HDD Recovery Tool included (NEC Instant Recovery)

Anti-theft ring

Kensington lock hole

Anti-theft for keyboard and mouse

Intrusion switch

Integrated hardware monitoring ASIC Optional Electromagnetic chassis lock

## POWER SUPPLY

SFF: 110/220V SFF: AC 220W - 50/60Hz Small Desktop : 110/220V AC - 250W - 50/60Hz Micro-Tower : 110/220V AC - 250W - 50/60Hz

#### **MONITORS**

NEC CRT 17"	Flat Screen FC17
	(17", VIS 16, 01", 0.27mm dp)
NEC LCD 17"	LC17m Black with integrated
	speakers (17", 17" VIS)
NEC LCD 19"	LC19m Black with integrated
	speaker (19", 19" VIS)

#### NEC ULTRACARE SOLUTIONS

Various Service Packages available\*

- Desktop installation and deployment Extended warranties
- Data Transfer
- Network connection

Please contact us for more information\*

#### S0FTWARE

Service Pack SP2
Internet Explorer 6,0 or latest
Adobe Acrobat Reader 7,0 or latest

Antivirus Norton Internet Security 2007
Direct X 9,0 or latest
Internet Plug in Flash - Shockwave -

Quick Time
Outlook Express XP Version

DVD Player (if Combo,
DVD & DVD+R9) Power DVD 7
Burning Software (if

(if -R9) Roxio Creator 9

Combo and DVD+R9) Roxio Creator 9
Microsoft Office Ready PC

#### BAYS

Ditto	
Small Form Factor	1 x 5.25" external Slim
	1 x 3.5" external Slim
	1 x 3.5" internal
Small Desktop	1 x 5.25" external
	1 x 3.5" external
	1 x 3.5" internal
Micro-Tower	2 x 5.25" external
	2 x 3.5" external
	2 x 3.5" internal

#### WARRANTY:

Warranty: 1 or 3 Years On Site D+1

(to choose)

Extended Warranty: 3 years On site D+1 Repair

Time Commitment \*
4 years On site D+1 Repair
Time Commitment \*
Extension to 4 Years On Site
D+1 \*
Extension to 4 Years On Site
D+1 Repair Time Commitment

D+1 Repair Time Commitment \*
Extension to 5 Years On Site
D+1 \*

\*not applicable in all countries, please contact reseller for more information

# REGULATORY & SAFETY

Regulatory Compliance: CE EMC Directive 89/336 ECC,

CE LVD Directive 73/23 ECC EN 55022 (98), EN 55024(98), EN 60950, CE Mark, RoHS support from FCS

# The latest manageability technology for professionals

PowerMate ML470 integrates Intel vPro technology to offer leading distance management functions as well as increased security. ML470 is combined with a BTX format motherboard which offers a lower noise level and a net energy consumption reduction. ML470 will satisfy both users and administrators.



# Manageability

- Inventory tasks possible even when the machine is switched off
- Remote power on / power off



## Security

- NEC Instant Recovery
- Optional electro-magnetic lock
- With vPro™ infected client stations within the network can be isolated



#### Performance

- Supports Intel Core 2 Quad processors
- Integrated RAID 0/1
- DDR2 667 and 800 MHz memory





















elease date : June 200

